

Heatsavr™

SDS Preparation Date (mm/dd/yyyy): 03/01/2016

Page 1 of 12

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: Heatsavr™

Product Code(s) : HS480, HS560, HS140
Recommended use of the chemical and restrictions on use

: Liquid swimming pool cover, that when added to your pool, creates a liquid barrier between

the water and the air for reducing the rate of evaporation.

No restrictions on use known.

Chemical family : Mixture of: Alcohols; Water

Name, address, and telephone number of

the supplier:

Name, address, and telephone number of

the manufacturer:

Refer to supplier

Flexible Solutions International

#206 - 920 Hillside Avenue Victoria, B.C., Canada

V8T 1Z8

Supplier's Telephone #

: (250) 477-9969; (800) 661-3560 (Toll Free) (Monday to Friday, 8 am to 4 pm, Pacific Time)

24 Hr. Emergency Tel # : (613) 996-6666 (CANUTEC)

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Light blue liquid. Solvent/alcohol odor.

Most important hazards:

Highly flammable liquid and vapor. This material may be ignited by heat, sparks and direct flame. Vapors are heavier than air and may spread along floors.

Causes eye irritation. Inhalation may cause central nervous system depression. Occupational exposure to the substance or mixture may cause adverse effects. For further information, please refer to section 11 of the SDS.

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Hazardous classification:

Flammable liquid - Category 2

Eye damage/irritation - Category 2B

Specific target organ toxicity, single exposure - Category 3 (Narcotic effects)

Label elements

Hazard pictogram(s)





Signal Word

DANGER!

Hazard statement(s)

Highly flammable liquid and vapor.

Causes eye irritation.

May cause drowsiness or dizziness.



Flexible Solutions International #206 - 920 Hillside Avenue Victoria, B.C., Canada, V8T 1Z8

Telephone: (250) 477-9969

Heatsavr™

SDS Preparation Date (mm/dd/yyyy): 03/01/2016

Page 2 of 12

SAFETY DATA SHEET

Precautionary statement(s)

Keep away from heat, sparks and open flame. - No smoking.

Keep container tightly closed.

Ground/Bond container and receiving equipment.

Use explosion-proof electrical and ventilating equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing vapors.

Wash hands and face thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves and eye/face protection.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes, Remove contact lenses, if present and easy to do, Continue rinsing. If eye irritation persists: Get medical advice/attention.

In case of fire, use dry chemical, CO2, or alcohol foam to extinguish.

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Dispose of contents/container in accordance with local regulation.

Other hazards

Other hazards which do not result in classification:

Toxic fumes may be released during a fire. May be mildly irritating to skin and respiratory system. May cause gastrointestinal irritation. Prolonged or repeated overexposure could cause adverse liver effects.

Environmental precautions:

Avoid release to the environment. See ECOLOGICAL INFORMATION, Section 12.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	Common name and synonyms	CAS#	Concentration (% by weight)
Ethanol	Ethyl alcohol Ethyl hydrate	64-17-5	82.19
Isopropanol	Isopropyl alcohol 2-Propanol	67-63-0	4.11

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

: Do not induce vomiting. Never give anything by mouth to an unconscious person. Get Ingestion

medical advice/attention.

Inhalation If inhaled: Remove person to fresh air and keep comfortable for breathing. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical

personnel only. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin contact : IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower. Wash contaminated clothing before reuse. If irritation or symptoms develop,

seek medical attention.

Eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Flush eyes with water for at least 15 minutes. If

eye irritation persists: get medical advice/attention.



Heatsavr™

SDS Preparation Date (mm/dd/yyyy): 03/01/2016

Page 3 of 12

SAFETY DATA SHEET

Most important symptoms and effects, both acute and delayed

: Causes eye irritation. Symptoms may include stinging, tearing, redness and swelling. Inhaling high concentrations may cause central nervous system depression, with effects ranging from dizziness and headache to unconsciousness.
May be mildly irritating to skin and respiratory system. May cause coughing and breathing difficulties. Direct skin contact may cause temporary redness.
Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Prolonged or repeated overexposure could cause adverse liver effects. Long-term ingestion may result in liver damage with symptoms such as jaundice, swelling of the legs, ankles and feet, weightloss and weakness. However, these effects and symptoms are primarily associated with the consumption of alcoholic beverages.

Indication of any immediate medical attention and special treatment needed

: Provide general supportive measures and treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

: Dry chemical, carbon dioxide and foam.

Unsuitable extinguishing media

: Water may be ineffective because it may not cool product below the flashpoint.

Special hazards arising from the substance or mixture / Conditions of flammability

: Highly flammable liquid and vapor. Will ignite when exposed to heat, flame and other sources of ignition. Vapors are heavier than air and collect in confined and low-lying areas. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106)

: Flammable liquid - Category 2

Hazardous combustion products

: Carbon oxides; formaldehyde; unburned alcohols.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire-fighting procedures

: Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

: Ensure spilled product does not enter drains, sewers, waterways, or confined spaces.

Methods and material for containment and cleaning up

: Ventilate the area. Prevent further leakage or spillage if safe to do so. Eliminate all ignition sources. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand). Pick up and transfer to properly labeled containers. Do not use combustible absorbents, such as sawdust. Refer to Section 13 for disposal of contaminated material. Contact the proper local authorities.



Heatsavr™

SDS Preparation Date (mm/dd/yyyy): 03/01/2016

Page 4 of 12

SAFETY DATA SHEET

Special spill response procedures

If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).

US CERCLA Reportable quantity (RQ): None known.

In Canada: Contact appropriate local and provincial environmental authorities for assistance and/or reporting requirements.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

: Use only outdoors or in a well-ventilated area. Wear protective equipment during handling. Wear protective gloves and eye/face protection. Avoid breathing vapors. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks and open flame. - No smoking. Ground/Bond container and receiving equipment. Use explosion-proof electrical and ventilating equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep away from incompatibles. Keep container tightly closed when not in use. Wash thoroughly after handling. Empty containers retain residue (liquid and/or vapour) and can be dangerous.

Conditions for safe storage

Store in a cool, dry, well-ventilated area. Store away from incompatibles and out of direct sunlight. Store locked up. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks.

Incompatible materials

 Strong oxidizing agents (e.g. hydrogen peroxide, nitric acid); Strong acids; Alkali metals (e.g. Sodium; Potassium)

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:					
Chemical Name	ACGI	HTLV	OSHA PEL		
	TWA	STEL	PEL	STEL	
Ethanol	N/Av	1000 ppm	1000 ppm (1900 mg/m³)	N/Av	
Isopropanol	200 ppm	400 ppm	400 ppm (980 mg/m³)	N/Av	

Exposure controls

Ventilation and engineering measures

: Use only outdoors or in a well-ventilated area. Use with adequate local or mechanical ventilation to meet TLV requirements. Use explosion-proof electrical and ventilating equipment.

Respiratory protection

If airbourne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

Skin protection

: Wear protective gloves. Wear as appropriate: Butyl rubber; Viton; Neoprene. The following glove material(s) are not recommended: Natural Rubber; polyvinyl alcohol; PVC. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Wear sufficient clothing to prevent skin contact.

Eye / face protection

: Wear eye/face protection. Wear as appropriate: Safety glasses with side shields; Tightly

fitting safety goggles.

Other protective equipment

An eyewash station and safety shower should be made available in the immediate working area. Other equipment may be required depending on workplace standards.



Heatsavr™

SDS Preparation Date (mm/dd/yyyy): 03/01/2016

Page 5 of 12

SAFETY DATA SHEET

General hygiene considerations

Avoid breathing vapors. Avoid contact with skin, eyes and clothing. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove soiled clothing and wash it thoroughly before reuse. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Light blue liquid. Odor Solvent/alcohol odor. Odor threshold 0.1 - 5100 ppm (Ethanol) 40 - 200 ppm (Isopropanol)

рΗ

Melting/Freezing point : - 100°C (- 148°F) (approximately)

Initial boiling point and boiling range

: 78 - 83°C (172 - 181°F)

13°C (55.4°F) Flash point Flashpoint (Method) Tag closed cup Evaporation rate (BuAe = 1) : 1.7 (butyl acetate = 1)

Flammability (solid, gas) Not applicable.

Lower flammable limit (% by vol.)

3.3%(Ethanol)

2.5% (Isopropanol)

Upper flammable limit (% by vol.)

19% (Ethanol) 12% (Isopropanol)

Oxidizing properties None known. **Explosive properties** Not explosive

5.9 kPa (44.25 mm Hg) @ 20°C (68°F) (Ethanol) Vapor pressure 4.41 kPa (33.1 mm Hg) @ 20°C (68°F) (Isopropanol)

Vapor density 1.61 (Air = 1)

Relative density / Specific gravity

: 0.7882 @ 20°C (68°F)

Solubility in water Complete

Other solubility(ies) Soluble in all proportions with diethyl ether, acetone, benzene, chloroform, methanol and

some other organic solvents.

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

N/Av

370°C (752°F) Auto-ignition temperature

Decomposition temperature : N/Av

Viscosity 1.35 cP @ 20°C (68°F) (approximately)

Volatiles (% by weight) 100% Volatile organic Compounds (VOC's) : 715 g/L

Absolute pressure of container

: N/Ap

Flame projection length : N/Ap Other physical/chemical comments

: No additional information.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.



Heatsavr™

SDS Preparation Date (mm/dd/yyyy): 03/01/2016

Page 6 of 12

SAFETY DATA SHEET

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions

: Hazardous polymerization does not occur.

: Ensure adequate ventilation, especially in confined areas. Avoid contact with incompatible Conditions to avoid

materials. Avoid heat and open flame.

Incompatible materials Strong oxidizing agents (e.g. hydrogen peroxide, nitric acid); Strong acids; Alkali metals (e.g.

Sodium; Potassium)

Hazardous decomposition products

: None known, refer to hazardous combustion products in Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES Routes of entry skin & eye : YES **Routes of entry Ingestion** : YES Routes of exposure skin absorption

: YES

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

Mild respiratory irritant. May cause coughing and breathing difficulties. Inhalation may cause headache, nausea and central nervous effects such as dizziness, coordination difficulties and unconsciousness.

Sign and symptoms ingestion

: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sign and symptoms skin Direct skin contact may cause slight or mild, transient irritation. Direct skin contact may

cause temporary redness.

Sign and symptoms eyes Causes eye irritation. Symptoms may include stinging, tearing, redness and swelling.

Potential Chronic Health Effects

Excessive over-exposure may cause slight liver effects. Long-term ingestion may result in liver damage with symptoms such as jaundice, swelling of the legs, ankles and feet, weightloss and weakness. However, these effects and symptoms are primarily associated

with the consumption of alcoholic beverages.

Mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Contains: Ethanol. Ethanol has been shown to cause mutagenic effects but at extremely

high oral doses, which are not applicable in an occupational setting.

Carcinogenicity Not expected to have carcinogenic effects. No components are listed as carcinogens by

ACGIH, IARC, OSHA or NTP.

Note that this product contains ethanol, a confirmed animal carcinogen (A3) by the ACGIH and human carcinogen (Group 1) by the IARC; however, this is only applicable when the chemical is present in alcoholic beverages.

Reproductive effects & Teratogenicity

This product is not expected to cause reproductive or developmental effects. Contains: Ethanol. Ethanol has been shown to cause effects on reproductive organs (e.g. decreased testicular weight, decreased numbers of motile sperm, decreased ovarian functions, irregular fertility cycles) but at extremely high oral doses, which are not applicable in an occupational setting. Ethanol has been shown to cause developmental / teratogenic effects, but only in the presence of maternal toxicity.



SDS Preparation Date (mm/dd/yyyy): 03/01/2016

Page 7 of 12

SAFETY DATA SHEET

Sensitization to material

Not expected to be a skin or respiratory sensitizer.

Specific target organ effects

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification:

Specific target organ toxicity, single exposure - Category 3. May cause drowsiness or

dizziness.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye and respiratory disorders.

Synergistic materials

Ethanol has been associated with an increase in the toxicity of many chemicals including other alcohols, ketones (e.g. acetone and methyl ethyl ketone), benzene, toluene, halogenated hydrocarbons (e.g. carbon tetrachloride, trichloroethylene, chloroform, and methylene chloride), aromatic amines and nitrosamines. In particular, it enhances the activity of many chemicals which are harmful to the liver (hepatotoxic agents). There is also a synergistic effect between ethanol and certain metals (e.g. cobalt, manganese and mercury) or compounds containing these metals.

Toxicological data

: Not classified for acute toxicity based on available data. The calculated ATE values for this mixture are:

ATE oral = 114,842 mg/kg

See below for individual ingredient acute toxicity data.

	LCso(4hr)	LD ₅₀		
Chemical name	inh, rat	(Oral, rat)	(Rabbit, dermal)	
Ethanol	> 32 380 ppm (61 mg/L) (vapor)	7060 mg/kg	> 15 800 mg/kg	
Isopropanol	17 000 ppm (41.8 mg/L) (vapor)	4720 mg/kg	12 890 mg/kg	

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: The product is not classified as environmentally hazardous. No data is available on the product itself. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters.

See the following tables for individual ingredient ecotoxicity data.

Ecotoxicity data:

In any all and a	0.0.0	Toxicity to Fish				
<u>Ingredients</u>	CAS No	LC50 / 96h	NOEC / 21 day	M Factor		
Ethanol	64-17-5	> 100 mg/L (Fathead minnow)	N/Av	None.		
Isopropanol	67-63-0	9640 mg/L (Fathead minnow)	N/Av	None.		





SDS Preparation Date (mm/dd/yyyy): 03/01/2016

Page 8 of 12

SAFETY DATA SHEET

<u>Ingredients</u>	CAS No	Toxicity to Daphnia				
		EC50 / 48h	NOEC / 21 day	M Factor		
Ethanol	64-17-5	5012 mg/L (Daphnia magna)	N/Av	None.		
Isopropanol	67-63-0	> 10 000 mg/L/24hr (Daphnia magna)	N/Av	None.		

<u>Ingredients</u>	CAS No	Toxicity to Algae				
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor		
Ethanol	64-17-5	1000 mg/L/96hr (Green algae)	N/Av	None.		
Isopropanol	67-63-0	N/Av	N/Av	None.		

Persistence and degradability

: No data is available on the product itself.

The following ingredients are considered to be readily biodegradable: Ethanol; Isopropanol.

Bioaccumulation potential

: No data is available on the product itself. See the following data for ingredient information.

Components	Partition coefficient n-octanol/water (log Kow)	Bioconcentration factor (BCF)
Ethanol (CAS 64-17-5)	- 0.31	N/Av
Isopropanol (CAS 67-63-0)	0.05	1.0

Mobility in soil

: No data is available on the product itself.

Other Adverse Environmental effects

 No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

: Handle waste according to recommendations in Section 7. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

Methods of Disposal

: Dispose in accordance with all applicable federal, state, provincial and local regulations.

RCRA

: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.



SDS Preparation Date (mm/dd/yyyy): 03/01/2016

Page 9 of 12

SAFETY DATA SHEET

SECTION 14. TRANSPORTATION INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
TDG	UN1987	ALCOHOLS, N.O.S. (Ethanol; Isopropanol)	3	II	3
TDG Additional information		as LIMITED QUANTITY when transported in containers no lai ss. Under the TDGR, refer to Section 1.17 for additional exem			
49CFR/DOT	UN1987	ALCOHOLS, N.O.S.	3	II	3
49CFR/DOT Additional information		as LIMITED QUANTITY when transported in containers no laises. Refer to 49 CFR Section 173.150.	l rger than 1.0 Liti	e, in packag	es not exceeding
ICAO/IATA	UN1987	Alcohols, n.o.s. (Ethanol; Isopropanol)	3	II	3
ICAO/IATA Additional Information	Refer to the app shipping this ma	propriate Packing Instruction, prior to shipping this material. Relaterial.	l view all State ar	d Operator	Variations, prior to
IMDG	UN1987	ALCOHOLS, N.O.S. (Ethanol; Isopropanol)	3	II	<u>₹</u>
IMDG Additional Information	May be shipped 30 kg gross mas	Las LIMITED QUANTITY when transported in containers no laises.	ger than 1.0 Liti	e, in packag	es not exceeding

Special precautions for user

: Appropriate advice on safety must accompany the package. Keep away from heat, sparks and open flame. - No smoking.

Environmental hazards

This product does not meet the criteria for an environmentally hazardous mixture, according to the IMDG Code. See Section 12 for more environmental information.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

Ingradianta	040 #	CERCLA Sec. 302, Extreme TSCA Reportable Hazardous			Specific Toxic Chemical		
<u>Ingredients</u>	CAS#	Inventory	Quantity(RQ) (40 CFR 117.302):	Substance, 40 CFR 355:	Toxic Chemical	de minimus Concentration	
Ethanol	64-17-5	Yes	None.	None.	No	N/Ap	
Isopropanol	67-63-0	Yes	None.	None.	Yes	1%	

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Fire Hazard; Immediate (Acute) health hazard; Chronic Health Hazard. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.



SDS Preparation Date (mm/dd/yyyy): 03/01/2016

Page 10 of 12

SAFETY DATA SHEET

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

Ingredients CAS #	CAS#	California Proposition 65		State "Right to Know" Lists					
	Grio "	Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Ethanol	64-17-5	Yes	Carcinogen (in alcoholic beverages)	Yes	Yes	Yes	Yes	Yes	Yes
Isopropanol	67-63-0	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

Canadian National Pollutant Release Inventory (NPRI): This product contains the following substances listed on the NPRI: Ethanol (Part 5: Individual Substances)

Isopropanol (Part 1, Group A Substance; Part 5: Individual Substances)

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	CAS#	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
Ethanol	64-17-5	200-578-6	Present	Present	(2)-202	KE-13217	Present	HSR001144
Isopropanol	67-63-0	200-661-7	Present	Present	(2)-207	KE-29363	Present	HSR001180

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists

AICS: Australian Inventory of Chemical Substances

CA: California

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of

1980

CFR: Code of Federal Regulations DOT: Department of Transportation

ENCS: Existing and New Chemical Substances EPA: Environmental Protection Agency

HMIS: Hazardous Materials Identification System HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer IATA: International Air Transport Association ICAO: International Civil Aviation Organisation IMDG: International Maritime Dangerous Goods

Inh: Inhalation

IOC: Inventory of Chemicals

IUCLID: International Uniform Chemical Information Database

KECI: Korean Existing Chemicals Inventory





SDS Preparation Date (mm/dd/yyyy): 03/01/2016

Page 11 of 12

SAFETY DATA SHEET

KECL: Korean Existing Chemicals List

LC: Lethal Concentration

LD: Lethal Dose MA: Massachusetts MN: Minnesota

mppcf: million particles per cubic foot

MSHA: Mine Safety and Health Administration

N/Ap: Not Applicable N/Av: Not Available

NFPA: National Fire Protection Association

NIOSH: National Institute of Occupational Safety and Health

NJ: New Jersey

NOEC: No observable effect concentration

OECD: Organisation for Economic Co-operation and Development

NTP: National Toxicology Program

OSHA: Occupational Safety and Health Administration

PA: Pennsylvania

PEL: Permissible exposure limit

PICCS: Philippine Inventory of Chemicals and Chemical Substances

PNOC: Particulates Not Otherwise Classified PNOR: Particulates Not Otherwise Regulated PNOS: Particles Not Otherwise Specified

RCRA: Resource Conservation and Recovery Act

RI: Rhode Island

RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments and Reauthorization Act SDS: Safety Data Sheet / Material Safety Data Sheet

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values TWA: Time Weighted Average TSCA: Toxic Substance Control Act

WHMIS: Workplace Hazardous Materials Identification System

References

- ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2015.
 - 2. International Agency for Research on Cancer Monographs, searched 2016.
 - Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2016 (Chempendium, HSDB and RTECs).
 - 4. Material Safety Data Sheets from manufacturer.
 - 5. US EPA Title III List of Lists March 2015 version.
 - 6. California Proposition 65 List December 4, 2015 version.
 - 7. OECD The Global Portal to Information on Chemical Substances eChemPortal, 2016.

Preparation Date (mm/dd/yyyy)

: 03/01/2016

Other special considerations for handling

: Provide adequate information, instruction and training for operators.



Heatsavr™

SDS Preparation Date (mm/dd/yyyy): 03/01/2016

Page 12 of 12

SAFETY DATA SHEET

Prepared for:

Flexible Solutions International #206 - 920 Hillside Ave. Victoria, B.C., Canada V8T 1Z8

Telephone: (250) 477-9969



Prepared by:

ICC The Compliance Center Inc.
Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada) http://www.thecompliancecenter.com



DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Flexible Solutions International and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Flexible Solutions International expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Flexible Solutions International.

END OF DOCUMENT