

MATERIAL SAFETY DATA SHEET  
FOR COATINGS, RESINS AND RELATED MATERIALS  
DATE OF PREPARATION - 01/01/10

PAGE #1

MANUFACTURER'S NAME : Kelley Technical Coatings  
ADDRESS : 1445 South 15th Street  
ADDRESS : PO Box 3726  
ADDRESS :  
CITY, STATE : Louisville, Kentucky, 40201-3726

EMERGENCY TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (800) 424-9300-  
INFORMATION TELEPHONE NO. DAY: (502) 636-2561- NIGHT: (502) 363-9721-

-----  
SECTION I -- PRODUCT IDENTIFICATION  
-----

MANUFACTURER'S CODE IDENTIFICATION : 820C  
PRODUCT CLASS : Epoxy Hardener  
TRADE NAME : SUPER X CONVOY CATALYST  
HMIS INFORMATION : HEALTH : 03  
FLAMMABILITY : 01  
REACTIVITY : 01  
PERSONAL PROTECTIVE EQUIPMENT : REFER TO "SECTION VIII"

-----  
SECTION II -- HAZARDOUS INGREDIENTS  
-----

----- INGREDIENT -----	%BY	ACGIH	OSHA	SAR	NUIS
MATERIAL DESCRIPTION Cas	WEIGHT	T.L.V.	P.E.L	313	PGMT
POLYOXYPROPYLENEDIAMINE					
9046-10-0	39.747			Y	N
AMINO ETHYL PIPERAZINE					
	30.443			N	N
NONYL PHENOL					
85852-12-3	29.810	5PPM	5PPM	Y	N

If indicated above; this material could constitute a personnel hazard.

If the CAS# field above starts with ## then this material is considered a trade secret.

-----  
SECTION III -- PHYSICAL DATA  
-----

LOWER EXPLOSION LEVEL	1.0 - 1.2	
BOILING RANGE	HIGH 567 DF	LOW 431 DF
VAPOR PRESSURE	0.01 MMHG @ 68DF	
VAPOR DENSITY	HEAVIER THAN AIR	
EVAPORATION RATE	SLOWER THAN BUTYL ACETATE	
WEIGHT PER GALLON	8.05	
% VOLATILE BY VOLUME	0	
% VOLATILE BY WEIGHT	0	
VOC --- LBS/GAL	0	LBS/GAL No Water 0
GRAMS/LITER	0	GRAMS/LITER 0

MATERIAL SAFETY DATA SHEET

PAGE #2

MANUFACTURER'S CODE 820C DATE OF PREPARATION - 01/01/10  
TRADE NAME SUPER X CONVOY CATALYST,

-----  
SECTION IV -- FIRE AND EXPLOSION DATA  
-----

FLAMMABILITY CLASSIFICATION OSHA - CLASS III-B  
DOT - NOT REGULATED  
LOWEST FLASH POINT T.C.C. 201 DF  
LOWER EXPLOSION LEVEL (LEL) N/A%  
Extinguishing Media: (Yes) - Foam (No) - Alcohol Foam (Yes) - CO2  
(Yes) - Dry Chemical (Yes) - Water Fog  
Unusual Fire and Explosion Hazards: - Flammable vapors may form explosive  
mixtures with air.  
Special Fire Fighting Procedures: - Avoid solid stream of water, use fog  
for cooling.

-----  
SECTION V -- HEALTH HAZARD DATA  
-----

To the best of our knowledge, this product does not  
contain any carcinogenic ingredients.  
Effects of Overexposure: - Liquid may cause eye burns. Prolonged skin  
contact with liquid may cause irritation. Eye, nose and throat  
irritation may result from exposure to vapor. Narcotic effects occur  
at higher concentrations of vapor.  
Primary Route(s) of Entry: (X) - Dermal (X) - Inhalation (X) - Ingestion  
Emergency and First Aid Procedures:  
- Eye contact: Irrigate immediately and thoroughly with water at least  
15 minutes and get medical attention.  
- Skin contact: Flush immediately and thoroughly with water.  
- Inhalation: Remove from exposure, treat symptomatically and get  
medical attention.  
Medical Conditions Prone to Aggravation by Exposure:  
- Pre-existing Respiratory, Eye and Skin Conditions.

-----  
SECTION VI -- REACTIVITY DATA  
-----

Stability: ( ) - Unstable (X) - Stable  
Hazardous Polymerization: ( ) - May Occur (X) - Will Not Occur  
Hazardous Decomposition Products: - As with any other organic material,  
combustion will produce carbon dioxide and probably carbon monoxide.  
Conditions to Avoid: - Not applicable.  
Incompatibility (Materials to Avoid): - Oxidizing materials can cause a  
vigorous reaction.

MATERIAL SAFETY DATA SHEET

PAGE #3

MANUFACTURER'S CODE 820C DATE OF PREPARATION - 01/01/10  
TRADE NAME SUPER X CONVOY CATALYST,

-----  
SECTION VII -- SPILL OR LEAK PROCEDURES  
-----

Steps to be Taken in Case Material is Leaked or Spilled:  
- Eliminate all ignition sources. Flush spill away with water spray.  
- Small spills may be collected with absorbant material.  
Waste Disposal Method:  
- Mix with a compatible chemical which is less combustibile and  
incinerate.  
- Observe all federal, state, and local laws concerning health and  
pollution.

-----  
SECTION VIII -- SAFE HANDLING AND USE INFORMATION  
-----

Respiratory Protection: - A NIOSH approved respirator for organic vapors  
should be worn if needed.  
Ventilation: - Local exhaust recommended.  
- Mechanical (General) recommended.  
- Special: None known.

Protective Gloves: - Should be worn.

Eye Protection: - Safety glasses should be worn in any type of industrial operation.

Other Protective Equipment: - Safety shower and eye bath in work area.

Hygienic Practices: - Remove paint from skin contact after exposure.

---

SECTION IX -- SPECIAL PRECAUTIONS

---

Precautions to be Taken in Handling and Storing: -

Keep away from heat, sparks and open flame.

Keep container closed. Avoid eye contact, prolonged skin contact, and inhalation of high concentrations of vapor. Use with ventilation adequate to maintain vapor concentrations below the TLV of 50 PPM.

Other Precautions: - Hazardous product residue may remain after the product has been removed from its container. Do not reuse "empty" container without commercial cleaning or reconditioning. See also 29 code of federal regulation 1910.1000.