# 16" SQUARE ANTI-ENTRAPMENT SUCTION OUTLET COVER FOR 12" SQUARE RETROFITS OR NEW CONSTRUCTION





Open Area 101in<sup>2</sup> For SOFA Specific Flow Ratings and specifications please scan QR code or visit www.aquastarpoolproducts.com/flowcode



#### **FEATURES**

Certified, Listed, and Labeled in conformance with APSP/ANSI/ICC-16 2017 and NSF/ANSI/CAN 50 standards

Easily and safely retrofits into most brands' existing 12" mud frames

Ideal for retrofitting over all existing sumps/ frames up to 15" by anchoring directly into concrete pool finish using four brass anchors and stainless screws in kit #BIK4

Manufactured from superior UV-resistant engineered polymers

#316 stainless steel screws

Trademarked VGBA compliance button easily identifies VGBA 2017 compliant cover from on deck and underwater

Online product support including downloadable CAD files, General Certificate of Conformity, third-party certificate, installation instructions and more

Replace drain cover every five years from the date of installation

See next page for additional product configurations

4 per case

# **1216** UNIVERSAL

HIGH-FLOW COVER FOR 12" MUD FRÂMES

Fits most brands' existing 12" mud frames.

Retrofits over all sumps/frames up to 15" using brass anchor kit.







Mud frame

Retrofit adapter frame for 3/4" deep 12" square retrofits

Retrofit adapter frame for 1" deep 12" square retrofits



Optional – extra screw holes for anchoring directly into pool finish using four brass anchor kit part # BIK4



Part # 1216xxx

Fits most brands' existing 12" mud frames. Retrofits over all sumps/frames up to 15" using brass anchor kit

#### STANDARD COLORS

1216101 – White

1216102 – Black


1216103 – Light Gray

1216105 – Dark Gray

1216108 – Tan

Also available as frame only p/n 12FRxxx 12 per case

VGBA 2017 Compliant



\*NOT ALL SCREWS & HARDWARE USED FOR ALL INSTALLATIONS.

10. #8 X 3/4" LG. Flat Head Phillips, Type A Screw, 316 SS, Qty 4

#### 6" Socket Deep PVC Sump




### **Open Area** 101in<sup>2</sup>

For SOFA Specific Flow Ratings and specifications please scan QR code or visit www.aquastarpoolproducts.com/flowcode







- 1. 12" Round Double Deep PVC Sump Bucket W/6" Socket
- 2. 12" To 16" Square Adapter Frame
   3. 16" Square Anti-Entrapment Suction Outlet Cover
- 4. #10 X 3/4" LG. Flat Head Phillips, Type A Screw, 316 SS, Qty 4 5. 10-32 X 1" LG. Pan Head Phillips, Machine Screw,
- 316 SS, Qty 4 6. Plug, 6" NPT

#### 3" Socket x 4" Spigot Side Port PVC Sump



Certified to NSF/ANSI/CAN 50 ANSI/APSP/ICC-16 2017

### **Open Area** 101in<sup>2</sup>

For SOFA Specific Flow Ratings and specifications please scan QR code or visit www.aquastarpoolproducts.com/flowcode



#### Hassle-free pressure testing and winterizing




1216xxxSSB 1 per case



Hassle-free pressure testing and winterizing Comes with a 3" and 2" NPT cap with O-ring. No knock-outs required.

2" Plug and O-Ring, p/n 2SBP101 3" Plug and O-Ring, p/n 3SBP101




1. Plug 2" Pipe THD.
2 Plug 3" Pipe THD.
3 O-Ring #340, 3350" ID x. 210" THK, EPDM
4 O-Ring, #238, 235" ID x. 125" THK, EPDM
5. Side Port Sump Bucket, 12" Square Frame
6. 10-32 X" 112. Pan Head Philips Screw, 316 5S, Qty 4
7. 12" Io 16" Square Suction Outlet Cover
8. 12" Io 16" Square Adapter Frame
9. #10 X 3/4" LG. Flat Head Phillips, Type A Screw, 316 SS, Qty 4


### **Adapter and Mud Frame Dimensions**

### **Mud Frame** 13-17/32 11-1/4 - 10-29/32 10-29/32 11-1/4 29/32 4x 3/8 Part # 12FRxxx 12 per case

# Retrofit Adapter Frame for 3/4" deep 12" square retrofits



# Retrofit Adapter Frame for 1" deep 12" square retrofits



Part # 12RFR1101 12 per case